

M-POWER-3T

AC POWER & DATA CONNECTIVITY SOLUTION

M-POWER-3TG1-AUA-G1AB

Distributed by



Mormax Company, Inc.

8 Westchester Plaza Elmsford, NY 10523

914-699-0101

sales@mormax.com mormax.com


Metro Light & Power's line of power & data solutions offers sophisticated design elements combined with greater ease of installation. Streamlined and low-profile, enhanced by side-exiting cords, our outlets advance the industry with their cutting-edge look and feel. We believe flexibility is key, and we provide a variety of mounting options, including the ability to mount in limited spaces. Our outlets are available in many finishes and configurations, in addition to a custom color and finish capability for our clients.

Bezel Finish:

UNICOLOR™ COOL GRAY (ABS)

Custom Finishes Available

M-POWER-3TG1-AUA-G1AB



Features:

Module/Port Options:

- Tamper Resistant AC Receptacle
- Double USB (Fast Charging Ports Rated for 3.2A)
- H HDMI
- 6 CAT 6
- 12 RJ 12
- X Switched AC
- Y 3-Way Switch
- C USB-C (27W High Speed Charging Port)
- Z USB-C (18W High Speed Charging Port)
- R Switched AC (Rocker Switch)

Supplied with Low Profile Flat 45° Angle 120 VAC Plug

Optional Standard Straight 120 VAC Plug

Optional Straight 120 VAC Pass-through Plug

Shown in Unicolor™ Cool Gray (ABS) Bezel, featuring 2 Tamper Resistant ACs, and 1 Double USB Charging Port.

- CLEAN, COMPACT DESIGN
- STREAMLINED
- LOW PROFILE
- SIDE-EXITING CORDS
- PLUG & PLAY
- 3.2A HIGH SPEED USB-A CHARGING FOR ALL DEVICES
- 6' AC CORD & PLUG (FLAT PLUG STANDARD)
- CUSTOMIZABLE CONFIGURATIONS AND FINISHES
- UL LISTED FOR MOUNTING IN FURNITURE
- 15A





Distributed by



Mormax Company, Inc.

914-699-0101 sales@mormax.com mormax.com

8 Westchester Plaza Elmsford, NY 10523

Specs:

Modules/Ports:

1.555" (39.503mm)

- Tamper Resistant AC Receptacle
- Double USB (Fast Charging Ports Rated for 3.2A)

TOP 1.381" (35.082mm) 2.106" (53.503mm) 4 Shown in Bezel, featuring 2 Tamper Resistant ACs, and 1 Double USB Charging Port. 3.861" (98.082mm) 5.570" (141.500mm) 6.319" (160.503mm) Optional Straight 120 VAC Pass-through Plug 0.619" 1.233" (31.340mm) (15.746mm) 0.984" 0.613" (15.594m 1.704" (43.300mm) Ø 1.132" (28.766mm) 2.515" (63.900mm) 1.381" (35.082mm) 0.234" (5.944mm) 0.118" (3.000mm) 1.840" (46.744mm) .606" (40.800mm) END SIDE

0.905" (23.000mm)