

M-POWER-4T

AC POWER & DATA CONNECTIVITY SOLUTION

4T-AAD-BRTP

Distributed by



Mormax Company, Inc.

8 Westchester Plaza Flmsford, NY 10523 **914-699-0101**

sales@mormax.com

mormax.com


Metro Light & Power's line of power & data solutions offers sophisticated design elements combined with greater ease of installation. Streamlined and low-profile, enhanced by side-exiting cords, our outlets advance the industry with their cutting-edge look and feel. We believe flexibility is key, and we provide a variety of mounting options, including the ability to mount in limited spaces. Our outlets are available in many finishes and configurations, in addition to a custom color and finish capability for our clients.

Plate Finish:

SOLID BRASS

Custom Finishes Available

M-POWER-4T-AAD-BRTP



Features:

Module/Port Options:

- A Tamper Resistant AC Receptacle
- U Double USB (Fast Charging Ports Rated for 3.2A)
- H HDMI
- 6 CAT 6
- 12 RJ 12
- X Switched AC
- Y 3-Way Switch
- C USB-C (27W High Speed Charging Port)
- Z USB-C (18W High Speed Charging Port)
- R Switched AC (Rocker Switch)
- D AC Rotary Dimmer Switch

Plug:

Supplied with Low Profile Flat 45° Angle 120 VAC Plug Optional Standard Straight 120 VAC Plug Optional Straight 120 VAC Pass-through Plug Shown in Solid Brass Plate, featuring 2 Tamper Resistant ACs and 1 AC Rotary Dimmer Switch

- CLEAN, COMPACT DESIGN
- STREAMLINED
- LOW PROFILE
- SIDE-EXITING CORDS
- PLUG & PLAY
- 6' AC CORD & PLUG (FLAT PLUG STANDARD)
- CUSTOMIZABLE CONFIGURATIONS AND FINISHES
- ETL LISTED (IN COMPLIANCE WITH UL 962A)
- 15A
- 0% TO 100% DIMMING



Distributed by



Mormax Company, Inc.

914-699-0101 sales@mormax.com

8 Westchester Plaza Elmsford, NY 10523

mormax.com

TOP Specs: **Modules/Ports:** 2.000" (50.800mm) Tamper Resistant AC Receptacle 2.106" (53.503mm) AC Rotary Dimmer Switch 7.240" (183.903mm) 7.559" (192.003mm) Shown with 2 Tamper Resistant ACs and 1 AC Rotary Dimmer Switch. Optional Straight 120 VAC Pass-through Plug 0.619" 1141" 0.984 (25.00m 1704" Ø 1.132" (28.766mm) 2.515" (63.900mm) 2.000" (50.800mm) 0.582" (14.800mm) 0.669" (17.000mm) 0.093" (2.381mm) 0.140" (3.563mm) 0.234" (5.944mm) 0.118" (3.000mm) 1 1.840" (46.744mm) .606" (40.800mm) END SIDE 0.905" (23.000mm) 1.555" (39.503mm)