

M-POWER-4T

AC POWER & DATA CONNECTIVITY SOLUTION

AT-ARAH-SATE

Distributed by



Mormax Company, Inc.

8 Westchester Plaza Flmsford, NY 10523 **914-699-0101**

sales@mormax.com


mormax.com

Metro Light & Power's line of power & data solutions offers sophisticated design elements combined with greater ease of installation. Streamlined and low-profile, enhanced by side-exiting cords, our outlets advance the industry with their cutting-edge look and feel. We believe flexibility is key, and we provide a variety of mounting options, including the ability to mount in limited spaces. Our outlets are available in many finishes and configurations, in addition to a custom color and finish capability for our clients.

Trim Plate Finish:

SATIN NICKEL (ABS)

Custom Finishes Available M-POWER-4T-ABAH-SATP



Features:

Module/Port Options:

- A Tamper Resistant AC Receptacle
- B USB-A & USB-C (3.0A USB-A / 15W USB-C)
- U Double USB-A (Fast Charging Ports Rated for 3.2A)
- D AC Dimmer
- H HDMI
- 6 CAT 6
- 12 RJ 12
- X Switched AC
- Y 3-Way Switch
- C USB-C (27W High Speed Charging Port)
- Z USB-C (18W High Speed Charging Port)
- R Switched AC (Rocker Switch)

Plug:

Supplied with Low Profile Flat 45° Angle 120 VAC Plug
Optional Standard Straight 120 VAC Plug
Optional Straight 120 VAC Pass-through Plug

Shown in Satin Nickel (ABS) Trim Plate, featuring 2 Tamper Resistant ACs, 1 USB-A & 1 USB-C Charging Port, and 1 HDMI Port.

- CLEAN, COMPACT DESIGN
- STREAMLINED
- LOW PROFILE
- SIDE-EXITING CORDS
- PLUG & PLAY
- 3.0A USB-A / 15W USB-C HIGH SPEED CHARGING FOR ALL DEVICES
- 6' AC CORD & PLUG (FLAT PLUG STANDARD)
- CUSTOMIZABLE CONFIGURATIONS AND FINISHES
- UL LISTED FOR MOUNTING IN FURNITURE
- 15A





Mormax Company, Inc.

914-699-0101

8 Westchester Plaza Elmsford, NY 10523

sales@mormax.com mormax.com


TOP Modules/Ports:


0.093" (2.381mm) 0.140" (3.563mm)


Tamper Resistant AC Receptacle USB-A & USB-C (3.2A USB-A / 15W USB-C)


HDMI

Specs:









0.234" (5.944mm)