

### M-POWER-5T

## MORMAX

Mormax Company, Inc.

914-699-0101

sales@mormax.com

#### 8 Westchester Plaza

Flmsford, NY 10523



### **AC POWER & DATA CONNECTIVITY SOLUTION** M-POWER-5T-AAUAA-SAB

Metro Light & Power's line of power & data solutions offers sophisticated design elements combined with greater ease of installation. Streamlined and low-profile, enhanced by side-exiting cords, our outlets advance the industry with their cutting-edge look and feel. We believe flexibility is key, and we provide a variety of mounting options, including the ability to mount in limited spaces. Our outlets are available in many finishes and configurations, in addition to a custom color and finish capability for our clients.

#### Bezel Finish:

#### **SATIN NICKEL (ABS)**

Custom Finishes Available

M-POWER-5T-AAUAA-SAB



#### Features:

#### **Module/Port Options:**

- A Tamper Resistant AC Receptacle
- B Double USB (Fast Charging Ports Rated for 3.2A)
- C HDMI
- D CAT 6
- E 3.5mm Mini Stereo Jack
- F Single USB (Fast Charging Port Rated for 3.2A)
- G RJ 12
- H Switched AC
  - 3-Way Switch
- J USB-C (27W High Speed Charging Port)
- K USB-C (13W High Speed Charging Port)
- L Switched AC (Rocker Switch)

Low Profile Flat 45° Angle 120 VAC Plug

Standard Straight 120 VAC Plug

- CLEAN, COMPACT DESIGN
- STREAMLINED
- LOW PROFILE
- SIDE-EXITING CORDS
- PLUG & PLAY
- 3.2A HIGH SPEED USB CHARGING FOR ALL DEVICES
- 6' AC CORD & PLUG (FLAT PLUG STANDARD)
- CUSTOMIZABLE CONFIGURATIONS AND FINISHES
- UL LISTED FOR MOUNTING IN FURNITURE
- 15A







## M-POWER-5T

### MORMAX

### **AC POWER & DATA CONNECTIVITY SOLUTION**

Mormax Company, Inc.

914-699-0101

8 Westchester Plaza

sales@mormax.com

Elmsford, NY 10523

mormax.com

M-POWER-5T-AAUAA-SAB

Specs:

# Modules/Ports: TOP Tamper Resistant AC Receptacle 1.381" (35.082mm) Double USB (Fast Charging Ports - Rated for 3.2A) 2.106" (53.503mm) 8.051" (204.500mm) 8.799" (223.503mm) 6.341" (161.082mm) Shown with 4 Tamper Resistant ACs, and 1 Double USB Charging Port. 0.619" (15.746mm) 1.233" (31.340mm) 0.613" (15.594mm) D 1.132" (28.766mm) 1.381" (35.082mm) 0.234" (5.944mm) 0.118" (3.000mm) .606" (40.800mm) END [ SIDE

0.905" (23.000mm)

1.555" (39.503mm)