

# M-POWER-5T

# **AC POWER & DATA CONNECTIVITY SOLUTION**

M-POWER-5T-ABA12H-BAB

Distributed by



Mormax Company, Inc.

8 Westchester Plaza Flmsford, NY 10523 **914-699-0101** 

sales@mormax.com

mormax.com


Metro Light & Power's line of power & data solutions offers sophisticated design elements combined with greater ease of installation. Streamlined and low-profile, enhanced by side-exiting cords, our outlets advance the industry with their cutting-edge look and feel. We believe flexibility is key, and we provide a variety of mounting options, including the ability to mount in limited spaces. Our outlets are available in many finishes and configurations, in addition to a custom color and finish capability for our clients.

Bezel Finish:

**BLACK (ABS)** 

Custom Finishes Available

M-POWER-5T-ABA12H-BAB



## Features:

#### **Module/Port Options:**

- A Tamper Resistant AC Receptacle
- B USB-A & USB-C (3.0A USB-A / 15W USB-C)
- U Double USB-A (Fast Charging Ports Rated for 3.2A)
- D AC Dimmer
- H HDMI
- 6 CAT 6
- 12 RJ 12
- X Switched AC
- Y 3-Way Switch
- C USB-C (27W High Speed Charging Port)
- Z USB-C (18W High Speed Charging Port)
- R Switched AC (Rocker Switch)

## Plug:

Supplied with Low Profile Flat 45° Angle 120 VAC Plug
Optional Standard Straight 120 VAC Plug
Optional Straight 120 VAC Pass-through Plug

Shown in Black (ABS) Bezel, featuring 2 Tamper Resistant ACs, 1 USB-A & 1 USB-C Charging Port, 1 RJ 12 Port, and 1 HDMI Port.

- CLEAN, COMPACT DESIGN
- STREAMLINED
- LOW PROFILE
- SIDE-EXITING CORDS
- PLUG & PLAY
- 3.0A USB-A / 15W USB-C HIGH SPEED CHARGING FOR ALL DEVICES
- 6' AC CORD & PLUG (FLAT PLUG STANDARD)
- CUSTOMIZABLE CONFIGURATIONS AND FINISHES
- UL LISTED FOR MOUNTING IN FURNITURE
- 15A



Distributed by



Mormax Company, Inc. 8 Westchester Plaza

Elmsford, NY 10523

914-699-0101 sales@mormax.com

mormax.com

# Specs: Modules/Ports: TOP Tamper Resistant AC Receptacle 1.381" (35.082mm) USB-A & USB-C (3.0A USB-A / 15W USB-C) 2.106" (53.503mm) 12 **RJ 12** HDMI UUUUUU 8.799" (223.503mm) 6.341" (161.082mm) 8.051" (204.500mm) Shown with 2 Tamper Resistant ACs, 1 USB-A & 1 USB-C Charging Port, 1 RJ 12 Port, and 1 HDMI Port. Optional Straight 120 VAC Pass-through Plug 0.619" (15.746mm) 1.233" (31.340mm) 1.141" 0.984 (25.00mm 0.613" (15.594mm) 1.704" (43.300mm) Ø 1.132" 2.515" (63.900mm) 1.381" (35.082mm) 0.234" (5.944mm) 1 0.118" (3.000mm) .606" (40.800mm) .840" (46.744mm) END SIDE

1.555" (39.503mm)

0.905" (23.000mm)