

M-POWER-5T

AC POWER & DATA CONNECTIVITY SOLUTION

5T-AARHX-RATE

Distributed by



Mormax Company, Inc.

8 Westchester Plaza Flmsford, NY 10523 **914-699-0101**

sales@mormax.com

mormax.com


Metro Light & Power's line of power & data solutions offers sophisticated design elements combined with greater ease of installation. Streamlined and low-profile, enhanced by side-exiting cords, our outlets advance the industry with their cutting-edge look and feel. We believe flexibility is key, and we provide a variety of mounting options, including the ability to mount in limited spaces. Our outlets are available in many finishes and configurations, in addition to a custom color and finish capability for our clients.

Plate Finish:

BLACK (ABS)

Custom Finishes Available

M-POWER-5T-AABHX-BATP



Features:

Module/Port Options:

- A Tamper Resistant AC Receptacle
- B USB-A & USB-C (3.0A USB-A / 15W USB-C)
- U Double USB (Fast Charging Ports Rated for 3.2A)
- H HDMI
- 6 CAT 6
- 12 RJ 12
- X Switched AC
- Y 3-Way Switch
- C USB-C (27W High Speed Charging Port)
- Z USB-C (18W High Speed Charging Port)
- R Switched AC (Rocker Switch)

Plug:

Supplied with Low Profile Flat 45° Angle 120 VAC Plug Optional Standard Straight 120 VAC Plug Optional Straight 120 VAC Pass-through Plug Shown in Black (ABS) Plate, featuring 2 Tamper Resistant ACs, 1 USB-A & USB-C Charging Port, 1 HDMI Port, and 1 Switched AC.

- CLEAN, COMPACT DESIGN
- STREAMLINED
- LOW PROFILE
- SIDE-EXITING CORDS
- PLUG & PLAY
- 3.0A USB-A / 15W USB-C HIGH SPEED CHARGING FOR ALL DEVICES
- 6' AC CORD & PLUG (FLAT PLUG STANDARD)
- CUSTOMIZABLE CONFIGURATIONS AND FINISHES
- UL LISTED FOR MOUNTING IN FURNITURE
- 15A



Distributed by



Mormax Company, Inc.


914-699-0101 sales@mormax.com


8 Westchester Plaza Elmsford, NY 10523


mormax.com

Specs: Modules/Ports:

- Tamper Resistant AC Receptacle
- USB-A & USB-C (3.0A USB-A / 15W USB-C)
- н **HDMI**
- Switched AC







0.093" (2.381mm) _\$ 0.140" (3.563mm) 0.118" (3.000mm) SIDE 0.905" (23.000mm)

0.234" (5.944mm)