

M-POWER-1TW-Y-SS4TP(2)

Distributed by



Mormax Company, Inc. 8 Westchester Plaza Elmsford, NY 10523

914-699-0101

sales@mormax.com


mormax.com

Metro Light & Power's line of power & data solutions offers sophisticated design elements combined with greater ease of installation. Streamlined and low-profile, enhanced by side-exiting cords, our outlets advance the industry with their cutting edge look and feel. We believe flexibility is key, and we provide a variety of mounting options, including the ability to mount in limited spaces. Our outlets are available in many finishes and configurations, in addition to a custom color and finish capability for our clients.

Trim Plate Finish: STAINLESS STEEL BRUSHED

Custom Finishes Available





Features:

Module/Port Options:

- Α **Tamper Resistant AC Receptacle**
- USB-A & USB-C (20W) Е
- Double USB-A (Fast Charging Ports 18W) M
- н HDMI
- CAT 6 6
- 12 RJ 12
- X Switched AC
- 3-Way Switch (Low Voltage) Y
- V USB-C (45W High Speed Charging Port)
- USB-C (25W High Speed Charging Port) S
- R Switched AC (Rocker Switch)
- **Dimmer Switch** D

Plug:

Supplied with Low Profile Flat 45° Angle 120 VAC Plug

Optional Standard Straight 120 VAC Plug

Optional Straight 120 VAC Pass-through Plug

CLEAN, COMPACT DESIGN

- STREAMLINED
- LOW PROFILE
- SIDE-EXITING CORDS
- **PLUG & PLAY**
- 6' AC CORD & PLUG (FLAT PLUG STANDARD)
- CUSTOMIZABLE CONFIGURATIONS AND FINISHES
- **UL LISTED FOR MOUNTING IN FURNITURE**
- 15A

UL LISTED AND APPROVED FOR USE ONLY WITH METRO LIGHT & POWER'S UL LISTED LEDS & CLASS 2 UL LISTED LED DRIVERS



METRO POWER M-POWER-1T AC POWER & DATA CONNECTIVITY SOLUTION

M-POWER-1TW-Y-SS4TP(2)

M-POWER-II W-1-3341P(2

Distributed by





Specs:

Modules/Ports:

3-Way Switch Shown with one 3-Way Switch. Female Barrel Jack (to Power Source/Metro UL Listed Male Barrel Jack (to LEDs) Class 2 LED Driver) 13 ft Connection Wire (connects the two outlets together) 3.519" (89.403mm) 3.838" (97.503mm) 2.000" (50.800mm) 2.106" (53.503mm) TOP Ι II 2.000" (50.800mm) 0.093" (2.381mm) 📫 0.234" (5.944mm) 0.140" (3.563mm) 0.118" (3.000mm) 1.840" (46.744mm) 1.606" (40.800mm) SIDE

1.555" (39.503mm)

END

0.905" (23.000mm)

