

#### AC POWER & DATA CONNECTIVITY SOLUTION

M-POWER-2T-XY-S3ATP(2)

Distributed by



Mormax Company, Inc.


914-699-0101

sales@mormax.com 8 Westchester Plaza mormax.com Elmsford, NY 10523

Metro Light & Power's line of power & data solutions offers sophisticated design elements combined with greater ease of installation. Streamlined and low-profile, enhanced by side-exiting cords, our outlets advance the industry with their cutting edge look and feel. We believe flexibility is key, and we provide a variety of mounting options, including the ability to mount in limited spaces. Our outlets are available in many finishes and configurations, in addition to a custom color and finish capability for our clients.

Trim Plate Finish: **GUNMETAL (ABS)** M-POWER-2T-XY-S3ATP(2)





#### Features:

#### **Module/Port Options:**

- **Tamper Resistant AC Receptacle**
- USB-A & USB-C (20W)
- Double USB-A (Fast Charging Ports 18W)
- HDMI
- CAT 6
- 12 RJ 12
- X Switched AC
- 3-Way Switch (Low Voltage)
- V USB-C (45W High Speed Charging Port)
- S USB-C (25W High Speed Charging Port)
- R Switched AC (Rocker Switch)
- **Dimmer Switch** D

### Plug:

Supplied with Low Profile Flat 45° Angle 120 VAC

Optional Standard Straight 120 VAC Plug

Optional Straight 120 VAC Pass-through Plug

- CLEAN, COMPACT DESIGN
- **STREAMLINED**
- LOW PROFILE
- SIDE-EXITING CORDS
- **PLUG & PLAY**
- 6' AC CORD & PLUG (FLAT PLUG STANDARD)
- **CUSTOMIZABLE CONFIGURATIONS AND FINISHES**
- **UL LISTED FOR MOUNTING IN FURNITURE**
- 15A

UL LISTED AND APPROVED FOR USE ONLY WITH METRO LIGHT & POWER'S UL LISTED LEDS & CLASS 2 UL LISTED LED DRIVERS





#### AC POWER & DATA CONNECTIVITY SOLUTION

M-POWER-2T-XY-S3ATP(2)

Specs:

# Distributed by



Shown with 1 Switched AC

Mormax Company, Inc.
8 Westchester Plaza

Elmsford, NY 10523

914-699-0101

sales@mormax.com
mormax.com

## Modules/Ports:

X Switched AC
Y 3-Way Switch

Female Barrel Jack
(to Power Source/UL Listed
Class 2 LED Driver)

13 ft Connection Wire
(connects the two outlets together)

