

AC POWER & DATA CONNECTIVITY SOLUTION

M-POWER-3TW-AEY-BZ5AATP(2)

Distributed by



Mormax Company, Inc. 8 Westchester Plaza

Elmsford, NY 10523

914-699-0101

sales@mormax.com mormax.com

Metro Light & Power's line of power & data solutions offers sophisticated design elements combined with greater ease of installation. Streamlined and low-profile, enhanced by side-exiting cords, our outlets advance the industry with their cutting edge look and feel. We believe flexibility is key, and we provide a variety of mounting options, including the ability to mount in limited spaces. Our outlets are available in many finishes and configurations, in addition to a custom color and finish capability for our clients.

Trim Plate Finish: ANTIQUED ARCHITECTURAL BRONZE (ABS)

Custom Finishes Available

M-POWER-3TW-AEY-BZ5AATP(2)





Features:

Module/Port Options:

- **Tamper Resistant AC Receptacle**
- USB-A & USB-C (20W)
- Double USB-A (Fast Charging Ports 18W)
- HDMI
- CAT 6 6
- 12 RJ 12
- X Switched AC
- 3-Way Switch (Low Voltage)
- USB-C (45W High Speed Charging Port)
- USB-C (25W High Speed Charging Port)
- R Switched AC (Rocker Switch)
- **Dimmer Switch** D

Plug:

Supplied with Low Profile Flat 45° Angle 120 VAC

Optional Standard Straight 120 VAC Plug

Optional Straight 120 VAC Pass-through Plug

- CLEAN, COMPACT DESIGN
- **STREAMLINED**
- LOW PROFILE
- SIDE-EXITING CORDS
- **PLUG & PLAY**
- 6' AC CORD & PLUG (FLAT PLUG STANDARD)
- **CUSTOMIZABLE CONFIGURATIONS AND FINISHES**
- **UL LISTED FOR MOUNTING IN FURNITURE**
- 15A

UL LISTED AND APPROVED FOR USE ONLY WITH METRO LIGHT & POWER'S UL LISTED LEDS & CLASS 2 UL LISTED LED DRIVERS





Specs:

AC POWER & DATA CONNECTIVITY SOLUTION

M-POWER-3TW-AEY-BZ5AATP(2)

Distributed by



Mormax Company, Inc. 8 Westchester Plaza

914-699-0101

mormax.com


sales@mormax.com

Elmsford, NY 10523

Modules/Ports: Tamper Resistant AC Receptacle Ε USB-A & USB-C (20W) 3-Way Switch

Shown with 1 Tamper Resistant AC, 1 USB-A & USB-C Charging Port, and one 3 Way Switch.

Female Barrel Jack Male Barrel Jack (to Power Source/UL Listed Class 2 LED Driver) (to LEDs) 13 ft Connection Wire (connects the two outlets together) 6.000" (152.403mm) 6.319" (160.503mm) 2.000" (50.800mm) 2.106" (53.503mm) TOP



0.093" (2.381mm) 0.140" (3.563mm) 0.234" (5.944mm) 0.118" (3.000mm) SIDE 0.905" (23.000mm)