

#### AC POWER & DATA CONNECTIVITY SOLUTION

M-POWER-4TG1-MVD-G1STP

Distributed by



Mormax Company, Inc.
8 Westchester Plaza

Elmsford, NY 10523

914-699-0101 sales@mormax.com


mormax.com

Metro Light & Power's line of power & data solutions offers sophisticated design elements combined with greater ease of installation. Streamlined and low-profile, enhanced by side-exiting cords, our outlets advance the industry with their cutting edge look and feel. We believe flexibility is key, and we provide a variety of mounting options, including the ability to mount in limited spaces. Our outlets are available in many finishes and configurations, in addition to a custom color and finish capability for our clients.

## Trim Plate Finish: UNICOLOR™ GRAY (ZINC/STEEL)

Custom Finishes Available

M-POWER-4TG1-MVD-G1STP



## Features:

### **Module/Port Options:**

- A Tamper Resistant AC Receptacle
- E USB-A & USB-C (20W)
- M Double USB-A (Fast Charging Ports 18W)
- H HDMI
- 6 CAT 6
- 12 RJ 12
- X Switched AC
- Y 3-Way Switch (Low Voltage)
- V USB-C (45W High Speed Charging Port)
- S USB-C (25W High Speed Charging Port)
- R Switched AC (Rocker Switch)
- Dimmer Switch

### Plug:

Supplied with Low Profile Flat 45° Angle 120 VAC Plug

Optional Standard Straight 120 VAC Plug

Optional Straight 120 VAC Pass-through Plug

- · CLEAN, COMPACT DESIGN
- STREAMLINED
- LOW PROFILE
- SIDE-EXITING CORDS
- PLUG & PLAY
- 6' AC CORD & PLUG (FLAT PLUG STANDARD)
- CUSTOMIZABLE CONFIGURATIONS AND FINISHES
- ETL LISTED FOR MOUNTING IN FURNITURE
- 15A





### AC POWER & DATA CONNECTIVITY SOLUTION

M-POWER-4TG1-MVD-G1STP

# Distributed by



Mormax Company, Inc.


 $\bigcirc$ 


914-699-0101


8 Westchester Plaza Elmsford, NY 10523 sales@mormax.com
mormax.com


# Specs: Modules/Ports:

- M Double USB-A (Fast Charging Ports 18W)
- V USB-C (45W High Speed Charging Port)
- D Dimmer Switch









0.093" (2.381mm) \$\frac{1}{2}\$
0.140" (3.563mm) \$\frac{1}{2}\$
0.118" (3.000mm) \$\frac{1}{2}\$

SIDE

0.234" (5.944mm)