

### AC POWER & DATA CONNECTIVITY SOLUTION

M-POWER-4TM2-AEAY-M2ATP(2)

Distributed by



Mormax Company, Inc.

 $\bigcirc$ 

914-699-0101 sales@mormax.com

mormax.com

8 Westchester Plaza Elmsford, NY 10523

Metro Light & Power's line of power & data solutions offers sophisticated design elements combined with greater ease of installation. Streamlined and low-profile, enhanced by side-exiting cords, our outlets advance the industry with their cutting edge look and feel. We believe flexibility is key, and we provide a variety of mounting options, including the ability to mount in limited spaces. Our outlets are available in many finishes and configurations, in addition to a custom color and finish capability for our clients.

Trim Plate Finish: UNICOLOR™ MAGNESIUM (ABS)

Custom Finishes Available M-POWER-4TM2-AEAY-M2ATP(2)





### Features:

## **Module/Port Options:**

- Tamper Resistant AC Receptacle
- E USB-A & USB-C (20W)
- M Double USB-A (Fast Charging Ports 18W)
- H HDMI
- 6 CAT 6
- 12 RJ 12
- X Switched AC

3-Way Switch (Low Voltage)

- V USB-C (45W High Speed Charging Port)
- S USB-C (25W High Speed Charging Port)
- R Switched AC (Rocker Switch)
- Dimmer Switch

## Plug:

Supplied with Low Profile Flat 45 $^{\circ}$  Angle 120 VAC Plug

Optional Standard Straight 120 VAC Plug

Optional Straight 120 VAC Pass-through Plug

- · CLEAN, COMPACT DESIGN
- STREAMLINED
- LOW PROFILE
- SIDE-EXITING CORDS
- PLUG & PLAY
- 6' AC CORD & PLUG (FLAT PLUG STANDARD)
- CUSTOMIZABLE CONFIGURATIONS AND FINISHES
- UL LISTED FOR MOUNTING IN FURNITURE
- 15A

 $\Lambda$ 

UL LISTED AND APPROVED FOR USE ONLY WITH METRO LIGHT & POWER'S UL LISTED LEDS & CLASS 2 UL LISTED LED DRIVERS





Specs:

END

1.555" (39.503mm)

## AC POWER & DATA CONNECTIVITY SOLUTION

M-POWER-4TM2-AEAY-M2ATP(2)

# Distributed by



Mormax Company, Inc.

©


914-699-0101

8 Westchester Plaza Elmsford, NY 10523

sales@mormax.com mormax.com

# Modules/Ports:

- A Tamper Resistant AC Receptacle
- E USB-A & USB-C (20W)
- Y 3-Way Switch



0.905" (23.000mm)