

AC POWER & DATA CONNECTIVITY SOLUTION

M-POWER-4TW-AMD-BRTP

Distributed by



Mormax Company, Inc.
8 Westchester Plaza

Elmsford, NY 10523

914-699-0101 sales@mormax.com


sales@mormo mormax.com

Metro Light & Power's line of power & data solutions offers sophisticated design elements combined with greater ease of installation. Streamlined and low-profile, enhanced by side-exiting cords, our outlets advance the industry with their cutting edge look and feel. We believe flexibility is key, and we provide a variety of mounting options, including the ability to mount in limited spaces. Our outlets are available in many finishes and configurations, in addition to a custom color and finish capability for our clients.

Trim Plate Finish Custom Finishes Available

Trim Plate Finish: **SOLID BRASS**

ble M-POWER-4TW-AMD-BRTP



Features:

Module/Port Options:

- A Tamper Resistant AC Receptacle
- E USB-A & USB-C (20W)
- M Double USB-A (Fast Charging Ports 18W)
- H HDMI
- 6 CAT 6
- 12 RJ 12
- X Switched AC
- Y 3-Way Switch (Low Voltage)
- V USB-C (45W High Speed Charging Port)
- S USB-C (25W High Speed Charging Port)
- R Switched AC (Rocker Switch)
- **D** Dimmer Switch

Plug:

Supplied with Low Profile Flat 45° Angle 120 VAC Plug

Optional Standard Straight 120 VAC Plug

Optional Straight 120 VAC Pass-through Plug

- CLEAN, COMPACT DESIGN
- STREAMLINED
- LOW PROFILE
- SIDE-EXITING CORDS
- PLUG & PLAY
- 6' AC CORD & PLUG (FLAT PLUG STANDARD)
- CUSTOMIZABLE CONFIGURATIONS AND FINISHES
- ETL LISTED FOR MOUNTING IN FURNITURE
- 15A





AC POWER & DATA CONNECTIVITY SOLUTION

M-POWER-4TW-AMD-BRTP

Distributed by



Mormax Company, Inc.

914-699-0101

sales@mormax.com
mormax.com


SONNECTIVITY SOLUTION


MD-BRTP


Elmsford, NY 10523


Specs: Modules/Ports:

- A Tamper Resistant AC Receptacle
- M Double USB-A (Fast Charging Ports 18W)
- D Dimmer Switch









0.093" (2.381mm) \$\frac{1}{0.140"} (3.563mm) \$\frac{1}{0.118"} (3.000mm) \$\frac{1}{0.905"} (23.000mm) \$

0.234" (5.944mm)