

M-POWER-5T-AMAYR-SS8B(2)

Distributed by



Mormax Company, Inc. 8 Westchester Plaza Elmsford, NY 10523 <u>5</u> 914-699-0101

] sales@mormax.com

🔗 mormax.com

Metro Light & Power's line of power & data solutions offers sophisticated design elements combined with greater ease of installation. Streamlined and low-profile, enhanced by side-exiting cords, our outlets advance the industry with their cutting edge look and feel. We believe flexibility is key, and we provide a variety of mounting options, including the ability to mount in limited spaces. Our outlets are available in many finishes and configurations, in addition to a custom color and finish capability for our clients.

## Bezel Finish: STAINLESS STEEL MIRROR FINISH Custom Finishes Available M-POWER-5T-AMAYR-SS8B(2) Features: Module/Port Options: CLEAN, COMPACT DESIGN **Tamper Resistant AC Receptacle** Α STREAMLINED USB-A & USB-C (20W) E LOW PROFILE Double USB-A (Fast Charging Ports - 18W) M SIDE-EXITING CORDS H HDMI **PLUG & PLAY** CAT 6 6 12 RJ 12 6' AC CORD & PLUG (FLAT PLUG STANDARD) Switched AC Х CUSTOMIZABLE CONFIGURATIONS AND FINISHES 3-Way Switch (Low Voltage) Y **UL LISTED FOR MOUNTING IN FURNITURE** USB-C (45W High Speed Charging Port) V 15A USB-C (25W High Speed Charging Port) S Switched AC (Rocker Switch) D **Dimmer Switch** D Plug: Supplied with Low Profile Flat 45° Angle 120 VAC Plug **Optional Standard Straight 120 VAC Plug Optional Straight 120 VAC Pass-through Plug**

N UL LISTED AND APPROVED FOR USE ONLY WITH METRO LIGHT & POWER'S UL LISTED LEDS & CLASS 2 UL LISTED LED DRIVERS



## METRO LIGHT& POWER M-POWER-5T

## AC POWER & DATA CONNECTIVITY SOLUTION

Modules/Ports:

Tamper Resistant AC Receptacle

M-POWER-5T-AMAYR-SS8B(2)

Α

Specs:

Distributed by



Mormax Company, Inc. 8 Westchester Plaza Elmsford, NY 10523

C 914-699-0101  $\square$ 

sales@mormax.com mormax.com

## Μ Double USB-A (Fast Charging Ports - 18W) Y 3-Way Switch Switched AC (Rocker Switch) R 1 Double USB-A Charging Port, one 3 Way Switch, and 1 Switched AC (Rocker Switch). М TRO Female Barrel Jack (to Power Source/UL Listed Class 2 LED Driver) Male Barrel Jack (to LEDs) 13 ft Connection Wire (connects the two outlets together) 6.341" (161.082mm) 8.051" (204.500mm) 8.799" (223.503mm) R. -J-TOP -)0(-T II 0 л. .... A 1.381" (35.082mm) 0.234" (5.944mm) 0.118" (3.000mm) 🛉 1.840" (46.744mm) .606" (40.800mm) END SIDE 0.905" (23.000mm) 1.555" (39.503mm)



2.106" (53.503mm) 1.381" (35.082mm)

© 2024 Metro Light & Power, LLC. All rights reserved. US Patent No(s) 10,841,990; 10,847,959; other Patents Pending Metro Light & Power, LLC | 11 Smith St Englewood, NJ 07631 | T: 201-416-4160 | F: 208-979-4613 | info@metrolightandpower.com | www.metrolightandpower.com